

<https://www.cyrusimap.org/3.0/imap/reference/manpages/systemcommands/cyradm.html>

Set ACLs on a mailbox. The ACL may be one of the special strings `none`, `read ( lrs )`, `post ( lrsp )`, `append ( lrsip )`, `write ( lrswipkxte )`, `delete ( lrxte )`, or `all ( lrswipkxte )`, or any combinations of the ACL codes:

**l**

Lookup (mailbox is visible to LIST/LSUB, SUBSCRIBE mailbox)

**r**

Read (SELECT/EXAMINE the mailbox, perform STATUS)

**s**

Seen (set/clear SEEN flag via STORE, also set SEEN flag during APPEND/COPY/FETCH BODY[...])

**w**

Write flags other than SEEN and DELETED

**i**

Insert (APPEND, COPY destination)

**p**

Post (send mail to mailbox)

**k**

Create mailbox (CREATE new sub-mailboxes, parent for new mailbox in RENAME)

**x**

Delete mailbox (DELETE mailbox, old mailbox name in RENAME)

**t**

Delete messages (set/clear DELETED flag via STORE, also set DELETED flag during APPEND/COPY)

**e**

Perform EXPUNGE and expunge as part of CLOSE

**a**

Administer (SETACL/DELETEACL/GETACL/LISTRIGHTS)